



LIMITED WARRANTY
4 YEAR | **400** HOUR

FASTRAK[®]

TOP-OF-THE-LINE RESIDENTIAL ZERO-TURN WITH A RUGGED FRAME, FORKS AND DECK

Ideal For Residential Estates & large acreage properties

HIGHLIGHTS

- 48", 54" or 60" commercial-style side-discharge deck
- Premium V-Twin FR Kawasaki engines
- Heavy-duty fabricated frame — unmatched durability
- Exclusive SmoothTrak™ steering — responsive, precise control
- Patented automatic parking brake
- Premium bolstered internal-suspension seat
- Commercial-grade transmission

LIMITED
LIFETIME WARRANTY
FRAME & LEADING EDGE OF DECK

The Hustler Fastrak has all the strength, durability and power needed for the pro-sumer or commercial operator. As proof, we offer a remarkable 4-year limited residential and commercial warranty plus limited lifetime warranties on the frame and leading edge of the deck.



ENGINE	
Manufacturer	Kawasaki FR691V, FR730V
HP	48" deck: 23HP* - FR691V 54" deck: 23HP* - FR691V 60" deck: 24HP* - FR730V
	* Per SAE J 1995
Displacement	726cc - Kawasaki
Cooling	Air cooled
Engine Warranty	3 yrs or 150hrs whichever comes 1st

DRIVE SYSTEM	
Type	Dual hydrostatic
Transmission	Hydro-Gear ZT-3100
Speed	8 mph (12.9 km/h)
Parking Brakes	Patented automatic

DECKS	
Cutting Width	Side discharge: 48", 54", 60"
Cutting Heights	1.5"- 4.5"
Deck Lift	Foot operated
Depth	5"
Blades	3
Blade Length	48" deck: 16.50" x 2.50" x .20" 54" deck: 18.50" x 2.50" x .20" 60" deck: 20.50" x 2.50" x .20"
Spindles	Aluminum with 1.0" shafts and sealed ball bearings
Drive	Electric PTO clutch
Construction	10 ga. fabricated
Spindle Mounts	Reinforced 11 ga.
Impact/Trim Areas	3/8" x 1" steel bar

CONSTRUCTION	
Frame	1.5" x 3" x .125" steel
Front Axle	Fabricated with sealed ball bearings
Front Caster Wheels	Heavy duty ball bearing, greasable
Front Caster Forks	Fabricated 3/8" steel

GENERAL	
Seat	Custom bolstered vinyl with internal suspension and arm rests
Fuel Capacity	5 gallons (18.9 L)
Cup Holder	Yes
Front Tyre	48": 13 x 5 - 6 smooth 54", 60": 13 x 6.5 - 6 smooth
Drive Tyre	48": 22 x 9.5 - 10, turf tread 54", 60": 22 x 11 - 10, turf tread

DIMENSIONS	
Weight	48": 835 lbs (378 kg) 54": 860 lbs (390 kg) 60": 885 lbs (401 kg)
Height	44.3" (1125.22 mm)
Length	73.6" (1869.44 mm)
Width w/ chute up	48": 49.1" (1064.26 mm) 54": 55.1" (1399.54 mm) 60": 61.1" (1551.94 mm)
Tire Width	48": 47" (1193.8 mm) 54", 60": 52" (1320.8 mm)

PRODUCTIVITY*	
Acres Per Hour	48": 3.10 54": 3.48 60": 3.88

OPTIONAL ACCESSORIES	
	Mulch kit
	2-bag power grass catcher
	LED lights
	FlexForks
	Steering extension kit
	Seat isolator kit

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.