

FASTRAK[®] SDX

STRONGER, FASTER, TOUGHER WITH COMMERCIAL-GRADE TRANSMISSION, UPGRADED CUSTOM SEAT AND MORE

HIGHLIGHTS

- 48", 54" or 60" commercial welded-steel deck
- Heavy-duty fabricated frame — unmatched durability
- Exclusive SmoothTrak[™] steering — responsive, precise control
- Patented automatic parking brake
- Heavy-duty cyclonic air cleaner
- Internal suspension seat with rubber isolated seat mounts

LIMITED
LIFETIME WARRANTY
FRAME & LEADING EDGE OF DECK

The Fastrak SDX is a true commercial grade mower, built for the prosumer or commercial operator who wants more of everything.

From zero-turning in tight spaces to covering straightaways at an industry-setting 14.5km/h. Most importantly, the Fastrak SDX delivers a professional cut every time. The Fastrak SDX has it all, and can do it all.



ENGINE	
Manufacturer	Kawasaki FX691V/FX730V
HP	48", 54" deck: 22HP* - FX691V 60" deck: 23.5HP* - FX730V * Per SAE J 1995
Displacement	726 cc
Cooling	Air cooled
Engine Warranty	2 yrs unlimited hrs

DRIVE SYSTEM	
Type	Dual hydrostatic
Transmission	Hydro-Gear ZT-3400
Speed	9 mph (14.5 km/h)
Parking Brakes	Patented automatic

DECKS	
Cutting Width	Side discharge: 48", 54", 60"
Cutting Heights	1.5" - 4.5"
Deck Lift	Foot operated
Depth	5"
Blades	3
Blade Length	48" deck: 16.5" x 2.5" x .20" 54" deck: 18.5" x 2.5" x .20" 60" deck: 20.5" x 2.5" x .20"
Spindles	Aluminum with 1.0" shafts and sealed ball bearings
Drive	Electric PTO clutch
Construction	10 ga. fabricated
Spindle Mounts	Reinforced 11 ga.
Impact/Trim Areas	3/8" x 1" steel bar

CONSTRUCTION	
Frame	1.5" x 3" x .125" steel
Front Axle	Fabricated with sealed ball bearings
Front Caster Wheels	Heavy duty ball bearing, greasable
Front Caster Forks	Fabricated 3/8" steel

GENERAL	
Seat	Custom bolstered vinyl with internal suspension and armrests
Fuel Capacity	5 gallons (18.9 L)
Cup Holder	Yes
Front Tyre	48": 13 x 5.0 - 5 rib tread 54", 60": 13 x 6.5 - 6 rib tread
Drive Tyre	48": 22 x 9.5 - 10 turf pattern 54", 60": 23 x 11 - 10 turf pattern

DIMENSIONS	
Weight	48": 835 lbs (378 kg) 54": 860 lbs (390 kg) 60": 885 lbs (401 kg)
Height	44.3" (1125.2 mm)
Length	48": 73.6" (1869.4 mm) 54": 74.42" (1890.2 mm) 60": 75.92" (1930 mm)
Width w/ chute up	48": 49.1" (1064.2 mm) 54": 55.1" (1399.5 mm) 60": 61.1" (1551.9 mm)
Tire Width	48": 47" (1193.8 mm) 54", 60": 52" (1320.8 mm)

PRODUCTIVITY*	
Acres Per Hour	48": 3.49 54": 3.93 60": 4.36

- OPTIONAL ACCESSORIES**
- Mulch kit
 - 2-bag power grass catcher
 - LED lights
 - FlexForks
 - Steering extension kit
 - High vacuum deck kit

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.