



LIMITED WARRANTY	2 YEAR	NO HOUR LIMIT
OR		
LIMITED WARRANTY	5 YEAR	500 HOUR

HUSTLER Z[®] DIESEL

THE POWER AND PRECISION OF A HUSTLER, THE STAMINA OF A DIESEL

HIGHLIGHTS

- 54", 60" or 72" side-discharge VX4[®] deck
- 60" rear-discharge deck
- Heavy-duty fabricated frame — unmatched durability
- Exclusive SmoothTrak™ steering — responsive, precise control
- Patented automatic parking brake
- Patented belt drive system provides up to three times longer belt life
- Clean, compact, service-friendly design



LIMITED
LIFETIME WARRANTY
FRAME & LEADING EDGE OF DECK

AVAILABLE AT CERTIFIED DEALERS

ENGINE	
Manufacturer	Shibaura
HP	25HP - Shibaura Tier 4
Displacement	1,131cc
Cooling	Liquid cooled, direct-drive, mechanical cooling fan
Air Cleaner	Heavy duty canister
Engine Warranty	3 yrs or 2,000 hours
DRIVE SYSTEM	
Type	Dual hydrostatic
Pumps	Tandem 21cc Hydro-Gear pumps
Wheel Motors	Parker TG0335
Hydraulic Lines	Stainless steel Parker seal loc technology
Hydraulic Cooling	Oil cooler with 8" fan (203 mm)
Reservoir Capacity	1.3 gallons (4.92 L)
Speed	12 mph (19.3 km/h)
Parking Brakes	Patented automatic
DECKS	
Cutting Width	Side discharge: 54", 60", 72" Rear discharge: 60"
Cutting Heights	1"- 5.5"
Deck Lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	54" deck: 3 - 18.50" x 3.00" x .203" 60" deck: 3 - 20.50" x 3.00" x .203" 72" deck: 3 - 24.50" x 3.00" x .250"
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1
Drive	Electric PTO clutch
Construction	11 ga. + 11 ga.+ 7 ga. welded steel
Spindle Mounts	Reinforced 11 ga. doubler + 7 ga. tripler, steel
Impact/Trim Areas	1.5" x .375" steel bar protector

CONSTRUCTION	
Frame	1.5" x 3.0" x .187" steel
Front Caster Wheels	Mounted with sealed ball bearings
Front Caster Forks	Fabricated 1/2" steel
GENERAL	
Seat	Grammer premium suspension seat, isolator platform
Fuel Capacity	14.4 gallons (54.5 L)
Cup Holder	Yes
Front Tire	13 x 6.5 - 6, rib tread
Drive Tire	54" deck: 24 x 9.5 - 12 60" & 72" deck: 24 x 12 - 12
DIMENSIONS	
Weight	54": 1645 lbs (746 kg) 60": 1695 lbs (768 kg) 72": 1760 lbs (798 kg)
Height w/ rops up	69" (1750 mm)
Height w/ rops Folded	51" (1300 mm)
Length	54" deck: 85.5" (2172 mm) 60" deck: 86.8" (2205 mm) 72" deck: 90.4" (2180 mm)
Width w/ chute up	54" deck: 59.25" (1505 mm) 60" deck: 66" (1676 mm) 72" deck: 78" (1981 mm)
Tire Width	54" deck: 52" (1400 mm) 60" & 72": 56" (1420 mm)
PRODUCTIVITY*	
Acres Per Hour	60": 5.57 72": 6.68
OPTIONAL ACCESSORIES	
	Mulch kit Light kit Semi pneumatic front tires FlexForks Steering extension kit Hydraulic deck lift Deck rear anti-scalp wheels Beacon kit Flasher kit Hitch kit

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.*