



LIMITED WARRANTY
3 YEAR | **NO** HOUR LIMIT

OR

LIMITED WARRANTY
5 YEAR | **500** HOUR

SUPER Z HYPERDRIVE®

INDUSTRY-EXCLUSIVE HYPERDRIVE® SYSTEM AND VX4® DECK TECHNOLOGY DELIVER UNRIVALED PERFORMANCE

HIGHLIGHTS

- 60", 66" or 72" VX4® deck — clean cut, excellent performance in all conditions
- Heavy-duty fabricated frame — unmatched durability
- Exclusive SmoothTrak™ steering — responsive, precise control
- Patented automatic parking brake
- HyperDrive® 5-year/3000-hour pump and motor warranty
- Six-way adjustable premium Grammer suspension seat with smooth ride isolator — all day comfort
- 16 mph (25.75km/h) top speed

5 YEAR | **3000** HOUR | PUMPS AND MOTORS

LIMITED
LIFETIME WARRANTY
FRAME & LEADING EDGE OF DECK



ENGINE	
Manufacturer	Kawasaki
HP	60" deck: 35HP* - FX1000 66" deck: 35HP* - FX1000 72" deck: 35HP* - FX1000 * Per SAE J1995
Displacement	999 cc
Cooling	Air cooled
Air Cleaner	Heavy duty canister
Engine Warranty	2 yrs unlimited hours
DRIVE SYSTEM	
Type	Dual hydrostatic
Pumps	Danfoss DDC-20
Wheel Motors	Parker TG280
Hydraulic lines	Stainless steel Parker seal loc technology
Hydraulic Cooling	Oil cooler with 9" fan
Reservoir capacity	3 gallons
Speed	16 mph (25.75 km/h)
Parking Brakes	Patented automatic
DECKS	
Cutting Width	Side discharge: 60", 66", 72" Rear discharge: 60"
Cutting Heights	1" - 5.5"
Deck Lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	60" deck: 3 - 20.5" x 3.0" x .25" 66" deck: 3 - 22.5" x 3.0" x .25" 72" deck: 3 - 24.5" x 3.0" x .25"
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1
Drive	Electric PTO clutch
Construction	11 ga.+ 11 ga.+ 7 ga. welded steel
Spindle Mounts	Reinforced 11 ga. doubler + 7 ga. tripler, steel
Impact/Trim Areas	1.5" x .375" steel bar protector

CONSTRUCTION	
Frame	1.5" x 3.0" x .187" steel
Front Caster Wheels	Mounted with sealed ball bearings
Front Caster Forks	Fabricated 1/2" steel
GENERAL	
Seat	Grammer suspension seat with isolator
Fuel Capacity	12 gallons (45.4 L)
Cup Holder	Yes
Front Tyre	13 x 6.5 - 6 rib tread, pneumatic
Drive Tyre	26 x 12 - 12, turf tread
DIMENSIONS	
Weight	60": 1745 lbs (792 kg) 66": 1775 lbs (805 kg) 72": 1805 lbs (818 kg)
Height w/ rops up	71.5" (1816 mm)
Height w/ rops Folded	54" (1370 mm)
Length	60" deck: 84.5" (2146 mm) 66" deck: 85.6" (2159 mm) 72" deck: 86.7" (2202 mm)
Width w/ chute up	60" deck: 66" (1676 mm) 66" deck: 72" (1828.8 mm) 72" deck: 78" (1981.2 mm)
Tire Width	60" deck: 57" (1447.8 mm) 66" deck: 60" (1524 mm) 72" deck: 60" (1524 mm)
PRODUCTIVITY*	
Acres Per Hour	60": 7.76 66": 8.54 72": 9.31
OPTIONAL ACCESSORIES	
	3-bag grass catcher (12 bushels) Mulch kit Hydraulic deck kit LED lights Semi pneumatic front tires FlexForks Steering extension kit Deck rear anti-scalp wheels Hitch kit Gator blades
<small>* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.</small>	