



LIMITED WARRANTY	2 YEAR	NO HOUR LIMIT
OR		
LIMITED WARRANTY	5 YEAR	500 HOUR

X-ONE[®]

COMMERCIAL ZERO-TURN MOWER BUILT FOR ALL-DAY, EVERY DAY PERFORMANCE

HIGHLIGHTS

- 48", 54" or 60" side-discharge decks
- Heavy duty canister style air cleaner
- 1.5" x 3" x 1.88" heavy-duty fabricated frame — unmatched durability
- Exclusive SmoothTrak™ steering — responsive, precise control
- Patented automatic parking brake
- Heavy-duty VX-4 deep commercial deck
- Kawasaki V-Twin commercial-grade engines



LIMITED
LIFETIME WARRANTY
FRAME & LEADING EDGE OF DECK

We designed the X-ONE mainframe with heavy-gauge rectangular tubing for strength. Then we narrowed the body, allowing the X-ONE to carry three different deck sizes to meet any user's needs. With a top speed of 11m/h (17.7 km/h), the X-ONE makes quick work of the largest jobs.

ENGINE	
Manufacturer	Kawasaki FX691V, FX850V
HP	48" deck: 22HP* - FX691V 54" deck: 27HP* - FX850V 60" deck: 27HP* - FX850V * Per SAE J1995
Displacement	FX691V: 726 cc FX850V: 852 cc
Cooling	Air cooled
Air Cleaner	Heavy duty canister
Engine Warranty	2 yrs unlimited hours
DRIVE SYSTEM	
Type	Dual hydrostatic
Wheel Motors	Parker unitized 12cc/r ev pump & 15.9ci/r ev wheel motors
Hydraulic Cooling	Transmission mounted fans
Speed	11 mph (17.7 km/h)
Parking Brakes	Patented automatic
DECKS	
Cutting Width	Side discharge: 48", 54", 60"
Cutting Heights	1"- 5.5"
Deck Lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	48" deck: 3 - 16.50" x 2.5" x .20" 54" deck: 3 - 18.50" x 2.5" x .20" 60" deck: 3 - 20.50" x 2.5" x .20"
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1
Drive	Electric PTO clutch
Construction	10 ga. Fab. with 7 ga. wrappers
Spindle Mounts	48", 54", 60": 10 ga. with 7 ga. doubler, steel
Impact/Trim Areas	11 ga. formed channel with rolled edge

CONSTRUCTION	
Frame	1.5" x 3.0" x .188" steel
Front Caster Wheels	Mounted with sealed ball bearings
Front Caster Forks	Fabricated 1/2" steel
GENERAL	
Seat	Deluxe vinyl suspension seat with sliding adjustment and armrests
Fuel Capacity	10.3 US gallons (38.9 L)
Cup Holder	Yes
Front Tyre	13 x 6.5 - 6 rib tread
Drive Tyre	48" & 54" deck: 24 x 9.5 - 12 turf pattern 60" deck: 24 x 12.0 - 12 turf pattern
DIMENSIONS	
Weight	48": 1200 lbs (544 kg) 54": 1210 lbs (548 kg) 60": 1260 lbs (571 kg)
Height with rops up	71.25" (1724.7 mm)
Height with rops Folded	53" (1333.5 mm)
Length	48" & 54" deck: 80.8" (2052.3 mm) 60" deck: 83.25" (2114.6 mm)
Width	48" deck: 53.50" (1358.9 mm) 54" deck: 59.25" (1505.0 mm) 60" deck: 66.00" (1680.0 mm)
Tire Width	48" & 54" deck: 47" (1295.4 mm) 60" deck: 54" (1376.0 mm)
PRODUCTIVITY*	
Acres Per Hour	52": 5.52 54"RD5.73 60": 6.36 60"RD6.36 72": 7.64
OPTIONAL ACCESSORIES	
	3-bag grass catcher (12 bushels) Mulch kit LED lights Hitch kit FlexForks Suspension kit for seat (48") Semi-pneumatic front tyres Steering extension kit Deck rear anti-scalp wheels

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.